

**1    WHAT IS CLAIMED IS:**

2            1. A strap suspender for a brassiere having  
3            a body having  
4                a top edge,  
5                a bottom edge,  
6                two side edges,  
7                a hook integrally formed with the bottom edge of the body,  
8                a transverse lip transversely formed with the top edge of the body  
9            and having  
10                a thickness,  
11                a central slot defined through the transverse lip, and  
12                an opening communicating with the central slot,  
13                a through hole defined through the transverse lip and beside the  
14            central slot near one of the side edges,  
15                a pivot pin, and  
16                a nub formed on the transverse lip near the side edge opposite to  
17            the through hole, and  
18                a holder pivotally mounted on the body and having  
19                a pivot end,  
20                a holding end,  
21                an inner surface,  
22                a hole defined through the pivot end of the body and aligned with  
23            the through hole in the transverse lip, and  
24                a keeper formed on the inner surface of the holder, and having

1                   a top piece,  
2                   a bottom piece, and  
3                   a detent defined in the top piece of the keeper and shaped  
4 corresponding to the nub on the transverse,  
5                   wherein the pivot pin is mounted through the through hole and the hole,  
6 the distance between the top piece and the bottom piece is equal to the  
7 thickness of the transverse lip on the body.

8                   2. The strap suspender for a brassiere as claimed in claim 1, wherein  
9 the holder further comprises multiple teeth formed on the inner surface of the  
10 holder toward the body.